


KEMET Part Number: ALS71A183NF200
(A490TM183M200A)

ALS71, Aluminum Electrolytic, 18,000 uF, 20%, 200 VDC, -40/+85°C



General Information

Series:	ALS71
Dielectric:	Aluminum Electrolytic
Description:	Screw Terminal, Aluminum Electrolytic
RoHS:	Yes
Mounting:	Stud
AEC-Q200:	No
Notes:	Dimensions D And L Include Sleaving. MS (MxH) = M12x16. Mounting Clip (Sold Separately): V11

Dimensions

D	77mm +/-1mm
L	105mm +/-2mm
T	5.5mm +/-0.5mm
S	31.8mm +/-0.5mm
DT	13mm +/-0.5mm
LT	110.5mm
TD	10mm MIN
V	19mm NOM
Z	10mm NOM

Packaging Specifications

Weight:	690 g
Sleaving:	Yes
Packaging:	Tray

Specifications

Capacitance:	18,000 uF
Capacitance Tolerance:	20%
Voltage DC:	200 VDC, 230 VDC (Surge)
Temperature Range:	-40/+85°C
Rated Temperature:	85°C
Life:	20000 Hrs (Rated Voltage And Ripple Current At 85C), 40000 Hrs (Rated Voltage At 85C)
Resistance:	24 mOhms (100Hz 20C), 19 mOhms (10kHz 20C)
Ripple Current:	18.8 Amps (100Hz 85C), 23 Amps (10 kHz 85C)
Leakage Current:	6000 uA