



5SDD 36K5000

Old part no. DV 889B-3600-50

Rectifier Diode

Properties

- Industry standard housing
- Suitable for parallel operation
- High operating temperature
- Low forward voltage drop
- Explosive protection

Key Parameters

V_{RRM}	=	5 000	V
I_{FAVm}	=	3 638	A
I_{FSM}	=	45 000	A
V_{TO}	=	0.903	V
r_T	=	0.136	mΩ

Types

	V_{RRM}
5SDD 36K5000	5 000 V
Conditions:	$T_j = -40 \div 160\text{ °C}$, half sine waveform, $f = 50\text{ Hz}$

Mechanical Data

F_m	Mounting force	$50 \pm 5\text{ kN}$
m	Weight	1.2 kg
D_s	Surface creepage distance	49 mm
D_a	Air strike distance	28 mm




Fig. 1 Case



ABB s.r.o.

Novodvorská 1768/138a, 142 21 Praha 4, Czech Republic

tel.: +420 261 306 250, <http://www.abb.com/semiconductors>

Maximum Ratings			Maximum Limits	Unit
V_{RRM}	Repetitive peak reverse voltage $T_j = -40 \div 160\text{ }^{\circ}\text{C}$		5 000	V
I_{FAVm}	Average forward current $T_c = 85\text{ }^{\circ}\text{C}$		3 638	A
I_{FRMS}	RMS forward current $T_c = 85\text{ }^{\circ}\text{C}$		5 715	A
I_{RRM}	Repetitive reverse current $V_R = V_{RRM}$		110	mA
I_{FSM}	Non repetitive peak surge current $V_R = 0\text{ V}$, half sine pulse	$t_p = 8.3\text{ ms}$	48 070	A
		$t_p = 10\text{ ms}$	45 000	A
I^2t	Limiting load integral $V_R = 0\text{ V}$, half sine pulse	$t_p = 8.3\text{ ms}$	9 589 900	A ² s
		$t_p = 10\text{ ms}$	10 125 000	A ² s
$T_{jmin} - T_{jmax}$	Operating temperature range		-40 ÷ 160	°C
T_{STG}	Storage temperature range		-40 ÷ 160	°C

Unless otherwise specified $T_j = 160\text{ }^{\circ}\text{C}$

Characteristics		Value			Unit
		min	typ	max	
V_{T0}	Threshold voltage			0.903	V
r_T	Forward slope resistance $I_{F1} = 5\,969\text{ A}$, $I_{F2} = 17\,907\text{ A}$			0.136	mΩ
V_{FM}	Maximum forward voltage $I_{FM} = 4\,000\text{ A}$			1.430	V
Q_{rr}	Recovered charge $V_R = 100\text{ V}$, $I_{FM} = 2000\text{ A}$, $di_F/dt = -30\text{ A}/\mu\text{s}$		5 000		μC

Unless otherwise specified $T_j = 160\text{ }^{\circ}\text{C}$

Thermal Parameters			Value	Unit
R_{thjc}	Thermal resistance junction to case	double side cooling	9.2	K/kW
		anode side cooling	14.5	
		cathode side cooling	25.2	
R_{thch}	Thermal resistance case to heatsink	double side cooling	2.5	K/kW
		single side cooling	5.0	

Transient Thermal Impedance

Analytical function for transient thermal impedance

$$Z_{thjc} = \sum_{i=1}^4 R_i (1 - \exp(-t / \tau_i))$$

Conditions:

$F_m = 50 \pm 5$ kN, Double side cooled

Correction for periodic waveforms

180° sine:	0.5 K/kW
120° sine:	0.6 K/kW
60° sine:	0.9 K/kW
180° rectangular:	0.5 K/kW
120° rectangular:	0.6 K/kW
60° rectangular:	0.9 K/kW

i	1	2	3	4
τ_i (s)	0.9405	0.1146	0.0807	0.0071
R_i (K/kW)	5.73	2.25	0.87	0.34




Fig. 2 Dependence transient thermal impedance junction to case on square pulse




Fig. 3 Maximum forward voltage drop characteristics




Fig. 4 Surge forward current vs. pulse length, half sine wave, single pulse, $V_R = 0 \text{ V}$, $T_j = T_{jmax}$




Fig. 5 Surge forward current vs. number of pulses, half sine wave, $T_j = T_{jmax}$




Fig. 6 Forward power loss vs. average forward current, sine waveform, $f = 50$ Hz, $T = 1/f$




Fig. 7 Forward power loss vs. average forward current, square waveform, $f = 50$ Hz, $T = 1/f$




Fig. 8 Max. case temperature vs. aver. forward current, sine waveform, $f = 50$ Hz, $T = 1/f$




Fig. 9 Max. case temperature vs. aver. forward current, square waveform, $f = 50$ Hz, $T = 1/f$

Notes: