



SPECIFICATIONS:

1	TYPE:	Protected Li-ion Rechargeable Battery
2	MODEL NUMBER:	P2660C
3	BATTERY CAPACITY:	Nom. 6000mAh discharge at 0.2C Min. 5900mAh discharge at 0.2C
4	NOMINAL VOLTAGE:	3.7V
5	OVER CHARGE PROTECTION VOLTAGE:	4.20V
6	OVER DISCHARGE PROTECTION VOLTAGE:	2.50V
7	OVER CURRENT PROTECTION CURRENT:	≥15A
8	SHORT CIRCUIT PROTECTION DELAY TIME:	280±84uS
9	STANDARD CHARGE CURRENT:	1200mA
10	MAXIMUM CONTINUOUS CHARGE CURRENT:	4000mA
11	STANDARD DISCHARGE CURRENT:	1200mA
12	MAXIMUM CONTINUOUS DISCHARGE CURRENT:	10A
13	MAXIMUM SIZE:	26.7(D)X69.7(L)mm
14	INTERNAL RESISTANCE:	≤50mΩ
15	MAXIMUM WEIGHT:	96g
16	OPERATION TEMPERATURE:	0°C~+45°C -20°C~+60°C
17	STORAGE TEMPERATURE:	Less than 1 month -20°C~+60°C -20°C~+45°C

CAUTION:

- 1 Do not short circuit the battery or dispose of in fire.
- 2 Do not immerse the battery in water or other liquids.
- 3 Do not disassemble.
- 4 Where a connector is present ensure connector polarity is correct.
- 5 Keep the battery out of reach of children.

NOTES:

- 1 BATTERY WITH BUILT IN PROTECTION CIRCUIT WHERE OFFER OVER DISCHARGE, OVER CHARGE AND SHORT CIRCUIT.
- 2 LABEL MUST BE PLACED ON BATTERY IN POSITION SHOWN ABOVE.

ITEM NO.	DESCRIPTION	QTY.	REVISIONS				CHECKED	KEEPPOWER TECHNOLOGY CO., LIMITED	www.keeppower.com	info@keeppower.com +86 769 82953418
1	Cell 26650-E600	1	REV.	DESCRIPTION	DATE	APPROVED				
1	KP-1S-2555-R Safety Circuit-PCM	1	A0	DP-111660-60M000	2025/04/03	Ray				
3	Heat Shrink	1								
4	Label P2660C-EU	1								
5	Top 24.1*1.7mm	1					PART NUMBER	SIZE	SHEET	1 OF 1
							P2660C	A4		