

IN32A589
INDUCTIVE SENSORS • INCREASED AMBIENT TEMPERATURE

sensor inductive, M32x1.5 83long, Non-flush, Sn: 13, 230°C, Other Anschluss an Verstärker, Cable 5m Polytetrafluorethylene (PTFE), IP50, Stainless steel 1.4305


MECHANICAL FEATURES

Active area material of sensor	Vectra®
Alignment of cable entry	Axial
Ambient temperature	-25 °C ... 230 °C
Cable infeed	Axial
Cable length	5 m
Degree of protection (IP)	IP50
Design	Cylinder, screw-thread
Housing material	Stainless steel 1.4305
Increased ambient temperatures > 80°C	+
Material of cable sheath	Polytetrafluorethylene (PTFE)
Mechanical mounting condition for sensor	Non-flush
Pressure-proof	-
Sensor length	83 mm
Thread pitch	1.5 mm
Thread size, metric	32

ELECTRICAL FEATURES

Cascadable	-
Connection to amplifier	+
Suitable for safety functions	-
Switching distance	13 mm
Type of electrical connection	Cable
Type of switching function	Amplifier
Type of switching output	Other
With monitoring function of downstream devices	-


Other

Packaging dimensions	138.0mm x 95.0mm x 210mm
Shipping weight	0.49kg
Tariff code	85365019

Classification

ipf product group	700
eClass 8.0	27270101
eClass 9.0	27270101
eClass 9.1	27270101
ETIM-5.0	EC002714
ETIM-6.0	EC002714
ETIM-7.0	EC002714

Connection



Dimensional drawing

Installation



Mounting / installation may only be carried out by a qualified electrician!

Disposal



Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information. Never use these devices in applications where the safety of a person depends on their functionality. LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.