


ESD PU CHAIR

Catalog number: RS-K4ESD-B



rtwork[®]
work equipment



AVAILABLE MODELS (by seat height range)



RS-K4ESD-A

Seat adjustment range:
480-610 mm



RS-K4ESD-B

Seat adjustment range:
560-750 mm



RS-K4ESD-C

Seat adjustment range:
610-870 mm


ESD PU CHAIR

Catalog number: RS-K4ESD-B




FUNCTIONS OF ADJUSTMENT


Seat height
adjustment



Backrest tilt
adjustment



Seat depth
adjustment



*dimensions shown in mm

Model	Height adjustment range [mm]	Total height [mm]	Total width [mm]	Seat dimensions [mm]	Backrest dimensions [mm]	Load capacity [kg]	Weight [kg]
RS-K4ESD-B	525 - 710	860 - 1120	640	465 - 440	130 - 420	120	10,7

MATERIALS

Material shade in reality may slightly differ from that presented in the catalog.

Comfort of use: Soft polyurethane seat and backrest with height adjustment ensures ergonomic comfort during work.

Safety: Antistatic properties compliant with ESD standards effectively protect against electrostatic discharge.

Durability: Chrome-plated steel base and dirt-resistant polyurethane guarantee long-term use in demanding environments.

Application: The Antistatic Polyurethane Chair is ideal for laboratories, service centers, and production environments where electrostatic control is essential.

Chair compliant with standards:

ANSI/ESD S.20.20.2014, PN-EN 1335-1:2004, PN-EN 1335-2:2009, PN-EN 1335-3:2009, PN-EN 1022:2007, PN-EN 61340-5-1:2024



ACCESSORIES:



+48 52 346 60 92 | +48 503 116 427



export@rtwork.pl | info@robtools.pl



www.rtwork-esd.com