

HDMI Audio Extractor 4K 60 Hz compact

Description

This adapter by Delock can be used to extract the audio signal from an HDMI transmission. While the video signal is displayed on a TV or monitor, the audio signal can be sent digital (S/PDIF) or analogue (stereo) to other devices, such as headphones or a surround receiver.



Item no. 63276

EAN: 4043619632763

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - Input:
 - 1 x HDMI-A 19 pin male
 - 1 x USB Type Micro-B female (5 V power supply)
 - Output:
 - 1 x HDMI-A 19 pin female
 - 1 x 3.5 mm 3 pin stereo jack female (audio)
 - 1 x TOSLINK female S/PDIF
- High Speed HDMI, 3D and HDCP 1.4 / HDCP 2.2
- Supports HDR (High Dynamic Range)
- Automatic switching to stereo (2.0) when using the stereo jack and automatic muting of the digital output
- Resolution up to 3840 x 2160 @ 60 Hz
- Video bandwidth up to 600 MHz / 6 Gbps, max. 18 Gb/s
- Supports all common 2.0 and 5.1 audio formats: LPCM, Dolby Digital, DTS Audio
- Supported sample rates: 16 / 20 / 24 bit, 32 / 44.1 / 48 / 88.2 / 96 kHz (depending on the system and the connected devices)
- HDMI audio routed to the output (pass-through)
- Power consumption: max. 2 W



System requirements

- A free HDMI-A female
- A free USB Type-A female port

Package content

- HDMI Audio Extractor
- USB Type-A to Type Micro-B cable, length ca. 30 cm
- User manual

Images



General

Specification:	DTS Audio Dolby Digital HDCP 1.4 HDCP 2.2 HDMI 2.0 HDR LPCM
----------------	---

Interface

Output:	1 x 3.5 mm 3 pin stereo jack female 1 x TOSLINK female 1 x HDMI-A female
Input:	1 x USB 2.0 Type Micro-B female 1 x HDMI-A male

Technical characteristics

Maximum screen resolution:	3840 x 2160 @ 60 Hz
Video bandwidth:	600 MHz / 6 Gbps

Physical characteristics

Housing colour:	black
Housing material:	Plastic

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de