



Catalog number: RS-K6ESD-A

## AVAILABLE MODELS (by seat height range )



**RS-K6ESD-A**

Seat adjustment range:  
430–555 mm



**RS-K6ESD-B**

Seat adjustment range:  
515–700 mm



**RS-K6ESD-C**

Seat adjustment range:  
560–810 mm

Catalog number: RS-K6ESD-A



## FUNCTIONS OF ADJUSTMENT

Seat height  
adjustment



\*dimensions shown in mm

Model	Height adjustment range [mm]	Total height [mm]	Total width [mm]	Seat dimensions [mm]	Backrest dimensions [mm]	Load capacity [kg]	Weight [kg]
RS-K6ESD-A	430 - 555	550 - 675	640	330 x 200	110 x 220	120	6,7

## MATERIALS

Material shade in reality may slightly differ from that presented in the catalog.

**Comfort of use:** Soft polyurethane seat with height adjustment ensures ergonomic comfort during work.

**Safety:** Antistatic properties compliant with ESD standards effectively protect against electrostatic discharge.

**Durability:** Chrome-plated steel base and dirt-resistant polyurethane guarantee long-term use in demanding environments.

**Application:** Ideal for laboratories, production lines, and technical workspaces. Used in electronics, automotive, medical, pharmaceutical, and industrial sectors.

### Chair compliant with standards:

ANSI/ESD S.20.20.2014, PN-EN 1335-1:2004, PN-EN 1335-2:2009, PN-EN 1335-3:2009, PN-EN 1022:2007, PN-EN 61340-5-1:2024



Poliurethane

## ACCESSORIES:



RS-KCZ/K1



RS-KCZ/K5



RS-KCZ/K7



RS-KCZ/K13



RS-KCZ/K13-B



RS-KPESD



RS-KZESD/P



RS-KZESD/B



RS-KZESD/R



RP-A235ESD



RP-A225ESD/HD