



F&F Filipowski sp.k., ul. Konstantynowska 79/81, 95-200 Pabianice, tel.: +48 (42) 214 90 37, e-mail: biuro@fif.com.pl, www.fif.com.pl



CDM-07

Smoke Detector

Index: CDM-07

The CDM-07 smoke detector is used for the early detection of fire hazards in enclosed spaces.



5 902431 678153 >

DESCRIPTION

Purpose

Equipped with an advanced optical sensor, it effectively responds to the presence of smoke with a loud audible and light alarm. With its compact housing and easy installation, it is ideal for installation in domestic environments.

The detector is not intended to be used in commercial or industrial premises as a control device for assessing compliance with the applicable standards.

The manufacturer will not be held liable for damage resulting from inappropriate or improper use.

The mechanical design of the detector protects against tampering by unauthorised persons. The high quality of the product is certified in accordance with EN14604:2005/AC1:2008.

The detector is designed to detect smoke, not to detect carbon monoxide or other gases.

Alarm procedure

In the event that the acceptable level of smoke is exceeded in the vicinity of the detector, an acoustic and light alarm will be reported. In such an event you should:

- Locate the smoke/fire origin.
- Extinguish the source of the flame. In the event of a larger hazard, notify the appropriate services immediately.
- Open doors and windows to remove the smoke.
- Leave the affected room.

The detector alarm will automatically switch off when the smoke concentration falls to a safe level.

TECHNICAL DATA

Loudness	85 dB
Diameter	105 mm
Height/depth	45 mm
Width	0 mm
Length	0 mm
Explosion-tested version	Nie
RAL-number (similar)	0
Rated switch current	0 A
Number of contacts as change-over contact	0
Number of contacts as normally open contact	0
Number of contacts as normally closed contact	0
With voltage indication	Tak
Supply voltage DC	9-9 V
Max. number networkable	0
Networkable via radio (optional)	Nie
Networkable via radiografic (standard)	Nie
Networkable via cable	Nie
Standalone	Tak
Smoke switcher	Tak
Response temperature	0 °C
Loudness	0 dB(A)
Acoustic notification	Tak
Optical notification	Tak
Degree of protection (IP)	IP40
Colour	White
Voltage type (operating voltage)	DC
Battery included	Alkaline
Voltage type (supply voltage)	DC
Current supply primary	Battery/accumulator
Mounting method	Other
Type of test-/pause button	Combination
Operating principle	Optical

Manual

CE declaration

Certificate

2025 Copyrights: www.fif.com.pl

e-mail: biuro@fif.com.pl